

## EXcel<sup>4</sup> Controller

### Networkable Access Control Unit

A versatile, networkable access control unit - the EXcel<sup>4</sup> is an extremely cost-effective solution to the access control and integrated security requirements of today.

It features supervised inputs and relays, making it suitable for monitoring and signalling alarm conditions as well as integration with intruder alarms and building management systems.

It also has an in-built TCP/IP port as standard to allow connection to modern IT networks, simplifying installation and commissioning.

### Features

- 18,000 card capacity
- 4 reader, 1 - 4 door controller
- Main reader output formats supported
- 4A mains power supply unit
- Standby battery facility
- Anti-Passback control
- 1000 event buffer
- Compatible with EXgarde PC / GARDiS software
- Robust enclosure design
- Integrated tamper switch
- Supports supervised inputs
- High capacity Form C changeover relays
- 3-year warranty



### Typical Installation Example



## Specification

EXcel <sup>4</sup>	
<b>TDSi Part No.</b>	5002-3092
<b>Dimensions</b>	390 x 410 x 90 mm
<b>Weight</b>	5.7 kg
<b>Operating Environment</b>	-5°C to + 45°C, 0 - 95% relative humidity (non-condensing)
<b>Power</b>	
<b>Input</b>	100-240 Vac, 50-60Hz, 1.8A max
<b>Output</b>	13.8Vdc (Nominal) (3A Max) 4 x 1A (Individually fused)
<b>Battery</b>	10.5 to 12.3Vdc 1 x 7Ah Sealed lead acid (optional)
<b>Features</b>	
<b>Max Credentials</b>	18,000
<b>Doors</b>	1, 2, 3 or 4
<b>Readers</b>	Maximum of 4; using the majority of reader, keypad and biometric technologies including those with standard clock & data, 26-bit Wiegand and HID standard 37-bit (H10302) output formats. For IR-technology only compatible with TDSi digital infrared readers.
<b>Inputs</b>	8 in total; 6 spare when used in 1 door mode, 4 spare when used in 2 door mode or 2 spare when used in 3 door mode for monitoring other equipment.
<b>Outputs</b>	4 changeover relay outputs (30V, 2A contact rating) 2 spare when used in 2 door mode for controlling other equipment.
<b>Time Groups</b>	64
<b>Anti-Passback</b>	Timed and true
<b>Mantrap Function</b>	Yes
<b>Communications</b>	RS232, RS485, Ethernet (TCP/IP)

## Ordering Information

EXcel <sup>4</sup>		
EXcel <sup>4</sup>	4 Reader Door Control Panel with Power Supply Unit and TCP/IP	5002-3092
EXcel <sup>4</sup> Assy	Door Control Panel Spare PCB Assembly	4165-3124

DS0009 - Issue 11