

Datasheet

ELECTRO-MAGNETIC LOCKS/ BO600RP - Magnetic Architectural Monitored Handle

Product description

Pull handles are becoming increasingly popular with sites that require strong holding forces or more aesthetic solutions. The entire range from CDVI is ideal for locations where a stronger lock is essential; such as schools, halls of residence and other public buildings.

The BO600RP & BO600RP3V are 2500mm handles incorporating 2x300kg or 3x300kg monitored magnets. It can be fitted to new or existing doors and can be used externally.

The handle can be fitted using either the REO spacer, the ALMA cable tray or the REOMA spacer and cable tray kit for a better finish. The unit can be cut and RAL colour options are available.

Key features

- Surface mount architectural handle
- Retrofit or new build
- Easy and quick installation
- Aesthetic profile
- Suitable for wood, metal & glass doors

**PATENTED
BREVETÉ**

DIAX



CE Certification

 DEEE

RoHS Certification

t -20°C to 70°C

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - September 2019 - CDVI_DS_BO600RP_A4_EN-01

Product Specifications

Holding force: 2x300kg or 3x300kg

Electrical Specifications

Operating voltage: 12V to 24Vdc

Current: @12Vdc = 550mA,
@24Vdc = 275mA

