



ENCLOSURE FOR CONTROL BOARDS 230V

Code JA320





Power supply (Vac)	230 (+6% -10%) – 50Hz
Absorbed power (W)	10
Max. motor load (W)	800
Accessories max. load (mA)	500
Electric lock max. load (VA)	15
Operating ambient temperature (°C)	-20 +55
Protection fuses	2
Function logics	Automatic/Semi-automatic/Safety/Semi-automatic B/ Dead Man C/Semi-automatic "Step by Step"
Opening / closing time	Programmable (from 0 to 120 sec.)
Pause time	0, 10, 20, 30, 60, 120 sec.
Closing leaf delay	0, 5, 10, 20 sec.
Opening leaf delay	2 sec. (can be excluded per dip-switch)
Thrust force	Adjustable per dip-switch on 8 levels for each motor
Terminal board inputs	Open/Open free leaf/Stop/Limit Switch/Opening and Closing Safety Devices/Power Supply + earth
Terminal board outputs	Flashing lamp/Motors/Accessories power supply 24Vdc/Failsafe/Electric lock 12Vac power supply
Quick-fit connector	Genius 5PIN receivers
Selectable functions	Logics and Pause times/ Thrust Force/ Opening and Closing Leaf Delay/ Reversing Thrust/ Failsafe/Closing Safety Device logic/ Pre-flashing
Programming key	Simple or Complete work times learning with or without limit switches or encoder, with or without slow-downs