

LBB4416/05 Network cable assembly, 5m

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Sturdy hybrid network cable
- ▶ Dual plastic optical fibers (POF) and copper power conductors
- ▶ Pre-assembled with connectors on both ends
- ▶ Low smoke/zero halogen (LSZH) sheet material
- ▶ Wide temperature range operation

The LBB4416/05 is a network cable with two plastic fibers for data communication and two copper cores for power supply. It is 5 meters long, and comes with connectors at both ends.

Certifications and approvals

Flame retardant	acc. to IEC 60332-1 60s
Halogen level	acc. to IEC 60754-2 pH >4.3, conductivity <10 uS/mm
Smoke level	acc. to IEC 61034-2 light transmission >60%

Region	Regulatory compliance/quality marks	
Europe	CE	DECL EC Accessories

Parts included

Quantity	Component
1	Network cable, 5 m

Technical specifications

Electrical

Wire	Copper, stranded 1 mm ²
Resistance	<0.018 ohm/m

Optical

Fiber	PMMA, 1 mm
Numeric aperture	0.5
Attenuation	<0.2 dB/m @ 650 nm
Bending loss	<0.5 dB (r=20 mm, 90°) JIS C6861

Mechanical

Diameter	7 mm (0.28 in)
Length	5 m (16.4 ft)
Color	Black
Pull force	150 N (max)

Environmental

Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)
Humidity	15% to 90%
Air pressure	600 to 1100 hPa

Ordering information

LBB4416/05 Network cable assembly, 5m
Praesideo hybrid network cable, 5 m length with network connectors.
Order number **LBB4416/05**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia