

# PR2000C

## 2000 Series - Accessory - Fp2000 Panel Printer Kit - Printer, Mounting Brackets, Connection Cables And Power Supply

### General

---

The PR2000C is a 40-column thermal printer with power supply. It is intended for use with all 2000C series fire panels and repeaters. The PR2000C is supplied with all necessary accessories and brackets to allow for easy installation inside the fire panel housing. The required 24 VDC and serial connection connect the printer to the fire panel hardware.

### Print Configuration

---

Because of the powerful printer configurations, the PR2000C may be used for event or report printing, with print filters allowing only the required data to be printed. In addition the configuration of the printer allows for only local panel events to be printed, or system events via the fire panel network, allowing for only a single printer allocated to multiple fire panels.

### Printer Supervision

---

When connected to a 2000C series fire panel or repeater, the power to the printer may be supplied from the fire panel power supply. Any problems with the printer, such as a disconnection or paper-out conditions, will be displayed on the fire panel.

### Printer Paper


---

In addition to fast and good quality printing, the PR2000C will allow printouts to be stored for more than 5 years without loss of readability.

### Codepage Support

---

International codepage support allows for printouts in all languages supported by the fire panel using the correct print character sets for special languages.



### Details

---

- Easy installation and configuration
- Power supplied from the fire panel
- May be used for Event or Report printing
- May be used as a Panel or System printer
- Full printer supervision from the fire panel
- Fast printing speed
- Good print quality
- Extended printout storage life
- International codepage support

# PR2000C

## 2000 Series - Accessory - Fp2000 Panel Printer Kit - Printer, Mounting Brackets, Connection Cables And Power Supply

### Technical specifications

---

#### Electrical

---

Operating voltage 18-36 VDC

---

Current consumption:

- Printer in standby 55 mA @ 24 VDC
  - Printer printing 930 mA @ 24 VDC
- 

#### Environmental

---

IP rating IP54

---

Operating temperature 0°C to +50°C

---

Storage temperature -10°C to +70°C

---

Relative humidity 10% to 80%  
(noncondensing)

---

#### Standards & regulation

---

Certification EN54-2

---

#### Physical

---

Dimensions (W x H x D) 87 x 61 x 42 mm

---

Weight 90 g

---

#### Data

---

Baud Rate 9600

---

Bit pattern 8, 1, n

---

Medium RS232

---

#### Paper

---

Number of columns 40

---

Print method Thermal

---

Resolution 203 DPI (8 dots/mm)

---

Paper specification Thermal roll, maximum external diameter 30 mm. Heat sensitive surface on the outside of the roll.

---

Paper weight 55 to 70 g

---

Paper width 57.5 mm

---

