

# TVK-800

TruVision IP Keypad, 7" LCD touch screen, 4-axis joystick, 12V DC, PoE

## Overview

---

The TVK-800 is a full featured IP keypad, designed to be used with the line of TruVision NVRs and DVRs. Using a TVK-800 allows you to efficiently control the monitor outputs of multiple recorders and decoders. Secondly, you can fully control every recorder's user interface using only the keypad.

## Full featured

---

TVK-800 provides a breadth of functionality. Physically the keypad can be controlled using the touch screen display, fully functional buttons, embedded touch pen, or 4-axis joystick. On the touch screen display it is possible to view live or recorded camera footage, configure recorder settings, or manage different views. The joystick allows you to smoothly control PTZ movement and navigate between menus. Lastly, the TVK-800 works on 12V DC but also on PoE-af, relieving the requirement for a separate power supply.



## Details

---

- Full featured IP keypad
- Control variety of NVRs, DVRs and decoders with one keypad
- Perform PTZ control
- Display IP cameras on embedded display
- Control recorder OSD
- Control monitor outputs of recorders
- Setting and calling presets & shadow tours
- 7" touch screen display
- 4-axis joystick
- Numeric and functional buttons
- PoE-af support
- Embedded touch pen

# TVK-800

TruVision IP Keypad, 7" LCD touch screen, 4-axis joystick, 12V DC, PoE

## Technical specifications

---

### General

---

Keyboard / controller type	IP
----------------------------	----

---

### Control

---

Joystick type	4-axis
Buttons	Numeric and functional

---

### User interface

---

Display type	7" TFT LCD touch screen
Embedded display resolution	800 x 480 pixels

---

### Audio

---

Audio output	1-ch, 3.5 mm connector (Linear, 600 Ohm)
Audio input	1-ch, 3.5 mm connector (2.0 Vp-p, 1 k Ohm)

---

### Interfaces

---

Connection interface	Ethernet
----------------------	----------

---

### Physical

---

Physical dimensions	193 x 435 x 110 mm
Net weight	2040 g
Colour	Black

---

### Environmental

---

Operating temperature	-10 to +50°C
Relative humidity	10 to 90%

---

### Electrical

---

Power supply type	12 VDC
Power supply value	12 V
Power consumption	<15 W

---

